


ADSS-48B1.1-PE-100M CABLE



Cable Section Sketch Map

1	Center Strength Member	FRP		
2	Fiber Unit	Loose tube	PBT	
		Fiber	48 Single Mode Fibers	G652D
		Fiber Quantity	12 Pcs Fibers× 4 Loose Tubes	
		Fiber Color	Blue、 Orange、 Green、 Brown、 Gray、 White 、 Red、 Black	
		Loose Tube Color	Blue、 Orange、 Green、 Brown、 Gray、 White	
		Filling (Fiber Jelly)	Thixotropic Jelly	
3	Water Blocking	Water Blocking Yarn		
4	Water Blocking	Water Blocking Tape		
5	Strength Member	Aramid Yarns		
6	Ripcord	1Pcs		
7	Outer Sheath	PE	10.3+/-0.5	

Technical Data Sheet

Item		Unit	Parameter
Cable Standard Weight		kg/km	80
Rated Tensile Strength(RTS)		N	4200
Maximum Allowable Tension(MAT)		N	1600
Every Day Strength(EDS)		N	1050
Min-Bending Radius	Short-Term	mm	20D
	Long-Term	mm	10D
Crush Performance	Short-Term	N/100mm	1000
	Long-Term	N/100mm	300
Suiting Line Voltage Class		Not more than 35 kV	
Span		m	100
Suitable Meteorological Condition		Max wind speed: 25m/s, No icing	
Operation	When working or in store	°C	-40°C+70°C
Temperature	When laying	°C	-10°C+50°C
Fiber Attenuation Coefficient in Cable		dB/km(1310nm)	≤0.36dB/km
		dB/km(1550nm)	≤0.22dB/km