

FTTX Fiber Management

JP0416S Fiber Access Terminal Closure

Description

JP-0416S fiber access termination closure is able to hold up to 16 subscribers and 96 splicing points as closure. It is used as a splicing closure and a termination point for the feeder cable to connect with drop cable in FTTX network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

- Water-proof design with IP-65 Protection Level.
- Integrated with flap-up splice cassette and adaptor holder
- All stainless metal plate and anti-rusting bolts, nuts
- Fiber bend radius control more than 40mm
- Suitable for the fusion splicer or mechanical splice
- 2Pcs of 1*8 Splitter can be installed as an option
- Mechanical sealing structure and mid-span cable entry.
- 16 ports cable entrance for drop cable
- 16 adapter for drop cable patching



Configuration

Materal	Size	Max Capacity		Nos of Adaptor	Wigh t	Color	
ABS/ PC	A*B*C(MM) 274*17 5*82	Splice Fibers (1trays, 16fiber/tray)	16	2pc of 1*8 PLC Splitter	16pc of SC	1.85 kg	Grey/b lack

Applications

- Wall mounting and pole mounting installation
- FTTH pre-installation and filed installation
- 2*3mm indoor FTTH drop cable and outdoor figure-8 FTTH self-supporting drop cable

Standard Accessories

Splice cassette and cable management tool, installation nuts and bolts, protection sleeves hose clamp, cable tube, wrench, cover, holder, rubber seal for cable entrance

Optional Accessories---Pole ring