

FTTX Fiber Management

FAP-16W-2 Fiber Access Terminal Closure

Description---FATM-0416MA fiber access termination closure is able to hold up to 16 subscribers and 24 splicing points as closure. It is used as a splicing closure and a termination point for the feeder cable to connect with drop cable in FTTX network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

- Features---**
- Water-proof design with IP-65 Protection Level.
 - Integrated with flap-up splice cassette and adaptor holder
 - All stainless metal plate and anti-rusting bolts, nuts
 - Fiber bend radius control more than 40mm
 - Suitable for the fusion splicer or mechanical splice
 - 2Pcs of 1*8 Splitter can be installed as an option
 - Mechanical sealing structure and mid-span cable entry.
 - 16 ports cable entrance for drop cable
 - 16 adapter for drop cable patching



Configuration

Material	Size	Max Capacity		Nos of Adaptor	Wight	Color
PC/ABS	A*B*C(MM) 290*210*78	Splice 16 Fibers (2traysX12F)	2pc of 1*8 PLC Splitter	16pc of SC	1.20kg	black

- Applications---**
- Wall mounting and pole mounting installation
 - FTTH pre-installation and filed installation
 - 2*3mm indoor FTTH drop cable and outdoor figure-8FTTH self-supporting drop cable

Standard Accessories---Splice cassette and cable management tool, installation nuts and bolts, protection sleeves hose clamp, cable tube, wrench, cover, holder, rubber seal for cable entrance