

FSTC-16QX Fiber Splitter Terminal Closure

Description

FSTC-16QX fiber splitter termination closure is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

- Water-proof design with IP-68 Protection level.
- Integrated with flap-up splice trays.
- Impact test:IK10,Pull Force:100N,Full rugged design.
- All stainless metal plate and anti-rusting bolts,nuts.
- Fiber bend radius control more than 32mm.
- 4x 12F splice trays,4 pcs of 1*16 PLC Splitters can be installed as an option.
- Plug-and-play installation, easy for maintenance and expansion.
- 180 degree access with 4pcs of buckled lock structure.
- 16x reinforced adapters for drop cable with reinforced connectors.
- 1x mid-span cable entrance for uncut cables (7-18mm). and 2x mechanical glands for distribution cable(7-18mm)



Configuration

Material	Size	Max Capacity	Nos of Reinforced Adaptor	Weight	Color
PP+GF	A*B*C(mm) 355*256*140	4x 12F splice trays (4pcs of 1x16 PLC splitter)	16 x Mini SC adapters	2.6kg	Black



Front view



Ports view



12F splice tray



Internal view

Standard Accessories

Splice trays x 4pcs, wall mounted kits, fiber protective sleeves, cable protection tube, manual.

Optional Accessories

Pole ring,Aerial hanging kit.